

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/027257 A1

- (51) International Patent Classification⁷: **F03B 13/26**, 15/00, 15/08
- (21) International Application Number: PCT/GB2003/003904
- (22) International Filing Date: 10 September 2003 (10.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0221896.4 20 September 2002 (20.09.2002) GB
- (71) Applicant (for all designated States except US): **SOIL MACHINE DYNAMICS LIMITED** [GB/GB]; Win-comblee Road, Newcastle Upon Tyne NE6 3QS (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **MANCHESTER, Jonathan, Ralph** [GB/GB]; 2 Cowell Grove, Rookswood, Rowlands Gill NE39 2JQ (GB).
- (54) Title: APPARATUS FOR GENERATING ELECTRICAL POWER FROM TIDAL WATER MOVEMENT
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



(57) Abstract: A tidally driven electricity generator (1) has a series of turbines (2), each of which is mounted under water in an offshore location. Each turbine (2) has blades (3) which are rotated by tidal flow of water, to power a respective generator (4), which outputs AC electrical power via a respective transformer (5) to a cable (6) and appropriate switchgear (7). The cable (6) is connected to a further transformer (8) located onshore, and the transformer (8) is connected to two AC inputs of a drive (9) containing an AC/DC converter, one input (10) of which is connected via a cable to a control feedback device (11). The control feedback device (11) may be a flow meter which determines the velocity of the tidal flow, or may contain look-up tables containing information relating to the velocity of tidal flow at any particular time. The drive (9) outputs DC electrical signals along cabling (13) to DC/AC converter (14), which outputs AC electrical power via transformer (15) to a fixed frequency local supply grid (16). The drive (9) also controls the speed of rotation of each turbine (2) by adjustment of the frequency of signals output to the turbines from the drive (9) via switchgear (7).